

PCT

REC'D 1 5 MAR 2005

INTERNATIONAL PRELIMINARY REPORT ON PATE WHABILITY PCT (Chapter II of the Patent Cooperation Treaty)

(PCT Article 36 and Rule 70)

Applicant's or agent's file reference	FOR FURTHER ACTION	See Form PC	T/IPEA/416		
PE17682PC00					
International application No.	International filing date (day/mon	nth/year)	Priority date (day/month/year)		
PCT/SE2002/002332	13-12-2002				
International Patent Classification (IPC) or national classification and IPC					
H04L 29/08, G06F 11/0	0, H04Q 7/38		1		
Applicant The Joseph Market LW Endergon (publ) et al					
Telefonaktiebolaget LM Ericsson (publ) et al					
 This report is the international preliminary examination report, established by this International Preliminary Examining Authority under Article 35 and transmitted to the applicant according to Article 36. 					
2. This REPORT consists of a total of 4 sheets, including this cover sheet.					
3. This report is also accompanied by ANNEXES, comprising:					
No. 10 10 10 10 2 shorts on follower					
,					
sheets of the description, claims and/or drawings which have been amended and are the basis of this report and/or sheets containing rectifications authorized by this Authority (see Rule 70.16 and Section 607 of the Administrative Instructions).					
sheets which supersede earlier sheets, but which this Authority considers contain an amendment that goes					
beyond the di	isclosure in the international appli	ication as filed,	as indicated in item 4 of Box No. I and the		
Supplemental Box.					
b. (sent to the International Bureau only) a total of (indicate type and number of electronic carrier(s))					
, containing a sequence listing and/or tables related thereto, in computer					
readable form only, as indicated in the Supplemental Box Relating to Sequence Listing (see Section 802 of the Administrative Instructions).					
 This report contains indications relating to the following items: Box No. I Basis of the report 					
Box No. II Priority			ļ		
Box No. III Non-establishment of opinion with regard to novelty, inventive step and industrial applicability					
Box No. IV Lack of unity of invention					
Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement					
Box No. VI Certain documents cited					
Box No. VII Certain	Box No. VII Certain defects in the international application				
Box No. VIII Certain	Box No. VIII Certain observations on the international application				
Date of submission of the demand	Date	of completion of	of this report		
\					
08-07-2004		24-02-2005			
Name and mailing address of the IPEA/SE		Authorized officer			
Patent- och registreringsverket Box 5055					
S-102 42 STOCKHOLM	Roc	ger Bou	Faisal /LR		
Facsimile No. +46 8 667 72 88		Telephone No. +46 8 782 25 00			

Form PCT/IPEA/409 (cover sheet) (January 2004)

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2002/002332

Box	No. I	Basis of the report			
1.	1. With regard to the language, this report is based on the international application in the language in which it was filed, unless otherwise indicated under this item.				
		This report is based on a translation from the original language into the following language, which is the language of a translation furnished for the purposes of:			
		international search (under Rules 12.3 and 23.1(b))			
		publication of the international application (under Rule 12.4)			
		international preliminary examination (under Rules 55.2 and/or 55.3)			
2.	furnisi	egard to the elements of the international application, this report is based on (replacement sheets which have been ed to the receiving Office in response to an invitation under Article 14 are referred to in this report as "originally filed" anot annexed to this report):			
-		the international application as originally filed/furnished			
	\boxtimes	the description:			
		pages 1-12 as originally filed/furnished			
		pages* received by this Authority on			
		pages* received by this Authority on			
	M	the claims:			
		pages as originally filed/furnished pages* as amended (together with any statement) under Article 19			
		pages* 1-3 received by this Authority on 05-01-2005			
		pages* received by this Authority on			
	\boxtimes	the drawings:			
	E3	pages 1-5 as originally filed/furnished			
		pages* received by this Authority on			
		pages* received by this Authority on			
		a sequence listing and/or any related table(s) - see Supplemental Box Relating to Sequence Listing.			
3.		The amendments have resulted in the cancellation of:			
		the description, pages			
		the claims, Nos.			
		the drawings, sheets/figs			
		the sequence listing (specify):			
		any table(s) related to the sequence listing (specify):			
4.		This report has been established as if (some of) the amendments annexed to this report and listed below had not been made, since they have been considered to go beyond the disclosure as filed, as indicated in the Supplemental Box (Rule 70.2(c)).			
		the description, pages			
		the claims, Nos.			
		the drawings, sheets/figs			
		the sequence listing (specify):			
		any table(s) related to the sequence listing (specify):			
*	If iten	4 applies, some or all of those sheets may be marked "superseded."			

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2002/002332

Box No. V Reasoned statement under Article 35(2) with regard to novelty, inventive step or industrial applicability; citations and explanations supporting such statement

1. Statement

Novelty (N) Claims 1-16 YES Claims NO Inventive step (IS) Claims 1-16 YES Claims NO Industrial applicability (IA) Claims 1-16 YES Claims NO

2. Citations and explanations (Rule 70.7)

The object of the invention is to achieve reliable and informative error messages for client-server communication through an intermediate device. The error status code sent from the server is transformed into an informative error description message including an extended error description text as well as a new status code.

Documents cited in the International Search Report:

D1: WO 0157666, A2 D2: US 6353855, B1 D3: US 2002126708, A1 D4: WO 02096063, A2 D5: US 6134680, A

Document D1 is considered to represent the closest prior art.

D1 relates to a method for generating error messages in a web based application, said method comprising the steps of searching said application for a predetermined error number; retrieving an error message corresponding to said error number; applying said error message to a style sheet in an error form; and displaying said error form on a requesting device (abstract; page 3, line 1- line 25; page 4, line 29-page 6, line 12; page 7, line 26-page 8, line 2; page 19, line 24-page 20, line 27; and claim 1).

The invention according to independent amended claims 1, 9 and 16 differs from D1 by transforming, at the intermediate device, the first status code into an error description message comprising an error description text and a second HTTP status

.../...

INTERNATIONAL PRELIMINARY REPORT ON PATENTABILITY

International application No.

PCT/SE2002/002332

Supplemental Box

In case the space in any of the preceding boxes is not sufficient. Continuation of: Box V

code. This step is performed in D1 by a processor in the Web Server and not by the intermediate server as in the claimed invention. Placing the processor and the error translation procedure in the intermediate device (Proxy server), which can be compared to the gateway function in D1, is an obvious step to a person skilled in the art. The object of the invention is to provide textual information to an end user describing the error.

However, the main objective of the present invention according to the amended claims is to overcome the problem of inadequate or misleading server-originating error information to the end user, which when using on external server or an MMSC, for example, may wrongly make the end user believe that the service is bad. Document D1, on the other hand, is concerned with providing a mechanism for formalized error handling and more user-friendly error messages.

In D2 there is described a procedure where the intermediate device, placed between a client sending requests to a server, is capable of translating and handling status descriptions based on the status indications and the determined characteristics of the users.

However, D2 does not suggest providing a new status code. The only status code presented is the first one, accompanying the original error message in the conventional way. D2 simply explains in a more user-friendly way what the first HTTP status code means.

The cited prior art documents are entirely focused on the content of the status description/error message to make it user friendly or capable of handling multilingual systems, and the control of the error information lies with the server device. D1 and D2 use one status code in a most conventional manner and contain no indication or suggestion pointing towards the solution claimed in accordance with the present invention.

Thus, the invention according to amended independent claims 1, 9 and 16 is novel and is considered to involve an inventive step.

1

PCT/SE2002/002332 05-01-2005

AMENDED CLAIMS

1. An error messaging method for a communication system where a wireless client terminal (10) communicates with a server (30) through an intermediate device (20), **characterized by** the steps of:

receiving, at the intermediate device (20), a first Hypertext Transfer Protocol (HTTP) status code from the server (30), the first status code being an error status code;

transforming, at the intermediate device, the first status code into an error description message comprising an error description text (24) and a second HTTP status code, the second status code indicating success and being associated with compulsory display of the error description text (24) at the client terminal (10); and

transmitting the error description message to the client terminal (10), whereby display of the error description text (24) at the client terminal (10) is enforced by the second status code.

- 2. The method of claim 1, **characterized in that** the transforming step in turn comprises extracting the error description message from an error information table (22) in response to input parameter information including the first status code.
- 3. The method of claim 2, **characterized in that** the input parameter information further includes a Uniform Resource Locator (URL) portion pointing to the server (30) and in that the extracted error description message is resource-location dependent.
- 4. The method of any of previous claims, **characterized in that** the transmitting step is performed by the intermediate device (20).
- 5. The method of any of previous claims, **characterized in that** the intermediate device (20) is selected from the group of an HTTP proxy and a Wireless Application Protocol (WAP) gateway.

30

5

10

15

20

25

- 6. The method of any of previous claims, **characterized in that** the server (30) is a Multimedia Messaging Service (MMS) center.
- 7. The method of claim 6, **characterized in that** the error description steps are initiated by a client request for a first MMS message and in that the error description message comprises a second MMS message.

10

15

20

25

30

- 8. The method of any or previous claims, **characterized in that** the error description text is displayed at the client terminal (10) by means of a language selected from the group of the Wireless Markup Language (WML) and the Hypertext Markup Language (HTML).
- 9. A proxy server (20) arranged between a wireless client terminal (10) and a server (30) in a communication system, **characterized by** error messaging means comprising:

means for receiving a first HTTP status code from the server (30), the first status code being an error status code;

means for transforming the first status code into an error description message comprising an error description text (24) and a second HTTP status code, the second status code indicating success and being associated with compulsory display of the error description text (24) at the client terminal (10); and

means for transmitting the error description message to the client terminal (10), whereby display of the error description text (24) at the client terminal (10) is enforced by the second status code.

10. The proxy of claim 9, **characterized in that** the means for transforming in turn comprises means for extracting the error description message from an error information table (22) in response to input parameter information including the first status code.

- 11. The proxy of claim 10, **characterized in that** the input parameter information further includes a URL portion pointing to the server (30) and in that the extracted error description message is resource-location dependent.
- 12. The proxy of any of claims 9-11, **characterized by** being selected from the group of an HTTP proxy and a WAP gateway.

5

- 13. The proxy of any of claims 9-12, **characterized by** communicating with a MMS center.
- 14. The proxy of claim 13, characterized in that the error description message comprises a MMS message.
- 15. The proxy of any of claims 9-14, **characterized in that** the error description text is displayed at the client terminal (10) by means of a language selected from the group of WML and HTML.
- 16. Error messaging means arranged in a MMS center (30) communicating with a wireless client terminal (10) through a proxy server (20), **characterized** by:

means for detecting an error related to an HTTP request from the client terminal (10);

means for generating an error description message comprising an HTTP status code for success and a MMS message (24) with an error description text based on the detected error, said status code being associated with compulsory display of the error description text at the client terminal (10); and

means for transmitting the error description message to the client terminal (10) through the proxy (20), whereby display of the error description text (24) at the client terminal (10) is enforced by the HTTP status code for success.